

VISION 250E & VECTOR 950E

VIRTUAL REALITY TRACKING SOLUTIONS MANUAL BASED PAN AND TILT HEADS

Virtual Reality Tracking Solutions
Manual Based Pan and Tilt Heads



Vision 250E

The Vision 250E combines a manually operated pan and tilt head with optical encoders, to provide precise real time digital electronic positioning of pan and tilt.

The Vision 250E tracking head provides the most complete link between an operator's desired performance from a pan and tilt head and the accuracy demanded for virtual applications.

The 250E is based on the award winning Vision 250 pan and tilt head, which uses a unique "twin spring balancing mechanism", to provide infinitely adjustable perfect balance throughout the tilt range.

Providing encoders to the Vision 250 head enables genuine high-end production capability for more budget sensitive needs such as webcasting, small studio productions and other on-location applications.

In addition the 250E retains the features of the Vision 250 such as the exceptional TF drag system, illuminated level bubble and back lit drag knobs, counterbalance positional display and an optional two-year warranty.

Vision 250IT

The Vision 250IT uses the Vision 250E, but includes an encoder capture board which provides positional data to the virtual set computer via a switchable RS-232 or RS-422 port, this is compatible with most virtual studio systems currently in use.

Vision 250SPI

The Vision 250SPI also uses the 250E as its base product. The addition of the new serial protocol interface box not only provides a single data stream to the rendering system, but also a direct interface to the modern lenses with encoder outputs, or the bolt on lens encoders ordinarily provided by Radamec or Vinten.

DRIVING THE FUTURE

Vector 950E

The Vector 950E combines the award winning manually operated Vector 950 pan and tilt head with optical encoders to provide precise real-time digital electronic positioning.

The Vector 950E has been specifically designed to meet the exacting demands of camera operators working in virtual production with full facility studio and OB cameras, offering a high level of control with many unique features.

The Vector 950E is fitted with very high quality rotary optical incremental encoders in both the pan and tilt

axis, and are accessed via a connector at the front of the head. Power to the encoders is 5V dc at 200mA maximum.

Vector 950SPI

The Vector 950SPI uses the 950E as its base product. The addition of the new serial protocol interface box not only provides a single data stream to the rendering system, but also a direct interface to the modern lenses with encoder outputs, or the bolt on lens encoders ordinarily provided by Radamec or Vinten.

Technical Specification

	Vision 250 E	Vector 950 E
Height	184mm / 7.2"	248mm / 9.7"
Length	160mm / 6.3"	225mm / 8.8"
Width	300mm / 11.8"	342mm / 13.5"
Weight	7.25kg / 16lbs	16.7kg / 36.8lbs
Tilt Range	± 90°	60kg payload to ±90° / 132lbs payload to ±90° 120kg payload to ±60° / 264lbs payload to ±60°
Capacity Range	10-33kgs / 22-73lbs	16-120kg / 35-264lb
Pan Resolution	802,560 counts per 360°	641,280 counts per 360°
Tilt Resolution	307,200 counts per 180°	319,015 counts per 180°
Encoder Power Requirements	5 volts dc ± 10%	5V dc ±10%

DRIVING THE FUTURE

info@vintenradamec.com

www.vintenradamec.com

CHINA
The Vitec Group plc China
Room 1806, Hua Bin Building,
No. 8 Yong An Dong Li,
Jian Guo Men Wai Ave,
Chao Yang District,
Beijing, P.R.China 100022
t +86 10 8528 8748
f +86 10 8528 8749

GERMANY
Camera Dynamics GmbH
Gebäude 16
Planiger Straße 34
55543 Bad Kreuznach
Germany
t +49 671 / 483 43 30
f +49 671 / 483 43 50

JAPAN
Vinten Japan KK
P.A. Bldg. 5F
3-12-6 Aobadai
Meguro-ku Tokyo 153-0042
Japan
t +81 3 5456 4155
f +81 3 5456 4156

UK
Camera Dynamics Ltd
Western Way,
Bury St Edmunds,
Suffolk IP33 3TB, UK
t +44 1284 752 121
f +44 1284 750 560
Sales Fax +44 1284 757 929

FRANCE
Camera Dynamics sarl
171, Avenue des Grésillons
92635 GENNEVILLIERS Cedex
France
t +33 820 821 336
f +33 825 826 181

Camera Dynamics GmbH
Erfurter Straße 16
85386 Eching
Germany
t +49 89 / 321 58 200
f +49 89 / 321 58 227

SINGAPORE
Camera Dynamics Pte Ltd
6 New Industrial Road,
#02-02 Hoe Huat Industrial
Building, Singapore 536199
t +65 6297 5776
f +65 6297 5778

USA
Camera Dynamics Inc.
709 Executive Blvd,
Valley Cottage, NY 10989, USA
t +1 845 268 0100
f +1 845 268 0113
Toll Free Sales 1 888 2 Vinten